

IN THE CLAIMS

At the top of the page, delete "Claims" and insert, at the left margin, "We Claim".

Amend the claims as follows:

Sub-C1 1. (Once Amended) [Process] In a process for the fashioning of a portion (3) of a profiled bead (2) extruded along a path onto an object, in particular a pane (1), in which process an initially shapeless mass (4) of material is produced in the portion (3) [in question] and is given the desired final shape by contact with a shaped surface of a moving tool (5), any excess material being automatically expelled from the tool in order to be removed, **[characterized in that]** the improvement wherein the mass (4) of material is produced by the superposition of two segments (2a, 2b) of the extruded strip, with the [following] steps of:

[-] [the] guiding an extrusion die (D) [is guided] along a first segment (2a) of the intended path of a profiled bead (2), including the portion (3) to be fashioned;

[-] moving the die (D) [is taken] away from the object (1) and, [is moved,] relative to the object (1), to an adjacent position of the portion (3) to be fashioned; and

[-] guiding the die (D) [is guided again,] along a second segment (2b) of the path of the profiled bead (2), also including the portion (3) to be fashioned.

2. (Once Amended) Process according to Claim 1 for the fashioning of a corner (3) in the profiled bead (2), especially in a corner of the object, **[characterized in that]** wherein the die (D) is moved relative to the object (1) by changing the relative orientation of the die (D) with respect to the object (1), especially by rotation through [the] a desired angle, **[and in that]** and by guiding the die (D) [is guided] in the new direction thus obtained.

3. (Once Amended) Process according to Claim 2, [**characterized in that**] wherein the first (2a) and/or second (2b) segment extend/extends beyond the perimeter of the object (1) so that the fashioned portion (3) projects beyond [the] an end face of the object (1).

4. (Once Amended) Process according to [any one of the preceding claims, **characterized in that,**] claim 1, wherein after the first segment (2a) has been extruded, the die (D) is moved by passing it over [that] a region of the first segment (2a) which includes the portion (3) to be fashioned.

5. (Once Amended) Process according to [any one of the preceding claims, **characterized in that**] claim 1, wherein the extrudable material continues to be delivered by the die (D) while the latter is being moved.

6. (Once Amended) Process according to [any one of the preceding claims, **characterized in that**] claim 1, wherein the moving tool (5) is applied against the portion (3) to be fashioned just after the die (D) has left that region of the second segment (2b) which includes this portion, in the actual extrusion station (E), without the object (1) being moved, transferred or repositioned.

7. (Once Amended) Process according to Claim 6, [**characterized in that**] wherein the moving tool (5) is automatically brought from a rest position to its working position immediately after the mass has been extruded and the extrusion die (D) has continued its travel, is automatically aligned with the profiled bead (2) and is brought into contact with the shapeless mass (4) in order to fashion it.

9. (Once Amended) Device according to [Claim 6, **being characterized by the** fact that] claim 8, wherein the means for adjusting the position comprise at least one laying face (17) to be applied against the object (1) and a bearing (10, 11) having a spherical movement allowing adjustment of the position parallel to one face of the object.

- 4 -

11. (Once Amended) Device according to Claim [9 or] 10, **[being characterized by the fact that]** wherein the tool (5) furthermore comprises a sealing rim (16) to be applied against a perimeter of the object.

12. (Once Amended) Device according to Claim 11, **[being characterized by the fact that]** wherein the sealing rim (16) and the laying face (17) are formed in a removable stop (15) fastened to the baseplate (12).

13. (Once Amended) Device according to [one of the previous device claims, **being characterized by the fact that]** claim 8, wherein the tool (5) comprises a punch (20) which can be moved by means of a cylinder (21) and has a surface for forming the profiled bead (2).

14. (Once Amended) Device according to Claim 13, **[being characterized by the fact that]** wherein a forming gasket (23) is fastened to the punch (20), which gasket, when the punch (20) is applied against the object, comes into contact with the top side of the latter and with the profiled bead, and the thickness of which gasket corresponds to the height of the profiled bead fashioned.

15. (Once Amended) Device according to [one of the previous device claims, **being characterized by the fact that]** claim 8, wherein the tool (5) includes a cutting edge (19) for cutting the excess material from the fashioned portion of the profiled bead (2).

16. (Once Amended) Device according to [one of the preceding device claims, **being characterized by the fact that**] claim 8, wherein the support frame (7) of the tool (5) is adjustable with respect to the treatment station (E) for various shapes of objects.

17. (Once Amended) Device according to device Claim 16, [**being characterized by the fact that**] wherein the actuating device includes a driving means (8) connected to the support frame (7).

18. (Once Amended) [Article] In an article, especially a window, comprising an object (1) provided with a profiled bead (2) extruded onto the object (1) and having a fashioned portion (3), [**characterized in that**] the improvement wherein the fashioned portion (3) consists of a continuous folded ribbon of extruded material, in which ribbon the contiguous surfaces of the fold or folds adhere to each other along a possibly pellicular interface, and which ribbon is fashioned by contact with a shaped surface.

19. (Once Amended) [Article] In an article, especially a window, comprising an object, especially a pane (1), provided with a profiled bead (2) extruded onto the object (1) and having at least one corner portion (3), [**characterized in that at**] the improvement wherein the at least one corner portion consists of the superposition of at least two partial beads (2a, 2b) which adhere to each other along a possibly pellicular interface, and which superposed bead is fashioned by contact with a shaped surface.